



Item 7113764

The Minimax 50 floor drain has a 50 mm side outlet and a low total height of 70mm (76mm with falls). It is suitable for installation in concrete joists. The Minimax floor drain comes complete with a removable NOOD water trap, clamping ring and plastic grate. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Item 7113764UK

The Minimax 50 floor drain has a 50 mm side outlet and a low total height of just 76mm. It is suitable for installation in concrete joists, as well as wooden joists when using a former tray or the Purus Plate. The Minimax 50 floor drain comes complete with a removable NOOD water trap, clamping ring, 50 mm to 1½" adapter for solvent weld and plastic grate for vinyl flooring. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. The floor drain is suitable for vinyl, tiled and resin flooring. Grates for tiled and resin floors are ordered separately.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping

ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

Item Number	7113764
Floor Construction	Concrete flooring
Floor Covering	Concrete/Resin/Tiles/Vinyl
Function	Side outlet
Item Color	White
Material	PP
Outlet Dimension	Ø50 mm
Pressure Flow Temp	0,8 l/s
Size	Ø130 mm
Version	With NOOD water trap

Item Number	7113764UK
Floor Construction	Concrete flooring
Floor Covering	Tiles
Function	Side outlet
Item Color	White
Material	PP

Outlet Dimension

Ø50 mm

**Pressure Flow
Temp**

0,8 l/s

Size

Ø130 mm

Version

With NOOD water trap

