


## Item 818912



Purus channel combo is made of acid-resistant stainless steel with side outlet Ø110 mm for installation in concrete. The floor channel is 300x300x200 och är avsedd för massagolv som ytskick. There is always residual water in the channel about 50 mm of water forms the water trap in the bottom of the channel and is equipped with a cleaning plug. The floor channel requires an almost continuous flow to function properly. Unsuitable in environments that set hygiene requirements.

## Item 818916

Purus channel combo is made of acid-resistant stainless steel with side outlet Ø110 mm for installation in concrete. The floor channel is 500x300x200 och är avsedd för massagolv som ytskick. There is always residual water in the channel about 50 mm of water forms the water trap in the bottom of the channel and is equipped with a cleaning plug. The floor channel requires an almost continuous flow to function properly. Unsuitable in environments that set hygiene requirements.

## Specifications

<b>Item Number</b>	818912
<b>Construction Height</b>	200
<b>Floor Construction</b>	Concrete flooring

<b>Floor Covering</b>	Resin
<b>Flow</b>	3,4
<b>Function</b>	Side outlet
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Outlet Dimension</b>	Ø110 mm
<b>Pressure Flow Temp</b>	3,4 l/s
<b>Size</b>	300x300x200
<b>Surface</b>	Pickled
<b>Version</b>	Do not forget grid/grating
<b>Item Number</b>	818916
<b>Construction Height</b>	200
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Resin
<b>Flow</b>	3,4
<b>Function</b>	Side outlet
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Outlet Dimension</b>	Ø110 mm

**Pressure Flow  
Temp**

3,4 l/s

**Size**

500x300x200

**Surface**

Pickled

**Version**

Do not forget grid/grating

Dimension (mm)	LxWxH (mm)	Ø (mm)
300x300x150	303 x 303 x 150	75
300x300x200	303 x 303 x 200	110
500x300x150	503 x 303 x 150	75
500x300x200	503 x 303 x 200	110

